

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

## **PMC - Panneau Multiplis de Construction**

according to the product specification listed in the current addendum to this certificate placed on the market by

### **Company**

**SCHILLIGER BOIS SAS**

**Route du port Rhenan**

**FR-68600 VOLGELSHEIM**

and produced in the manufacturing plant

**FR-68600 Volgelsheim, Route du port Rhenan**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

**ETA-18/0884, issued on 20.07.2020**

and

**EAD 130005-00-0304**

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

**Certificate number:** 1359-CPR-0882

**Date of first issue:** 26.05.2025

**Date of issuance:** 26.05.2025

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see [www.holzforchung.at](http://www.holzforchung.at).



**DI Bernhard Kraus**  
Authorised signatory



**PD Gerhard Grüll**  
Head of the Certification Body

## Addendum to certificate 1359-CPR-0882

Date of issuance: 26.05.2025

### Scope of certification:

### **PMC - Panneau Multiplis de Construction**

**Solid wood slabs to be used as structural elements in Building**

Structure:	min. 3-layers, layers arranged perpendicular (angle of 90°) max. 3 fibre-parallel outer layers with a total thickness of 90 mm
Strength classes of the laminations:	C 24 according EN 338
Thickness of the laminations:	9 mm – 50 mm
Thickness:	max. 480 mm
Width × length:	max. 3, 4 × 16,0 m
Classes of utilisation:	1, 2
Wood species:	PCAB – spruce /ABAL – fir
Adhesive:	
- Finger joints:	Type I: PUR according to EN 15425
- Surface bonding:	Type I: PUR according to EN 15425